



Technical data Universal low pressure hot cleaner 1000 ESR

Mobile universal spray cleaner with cleaning bath for parts, solid grid in stainless steel. Water Recycling via a special sedimentation system, with filter monitoring, pressure adjustment. All media contacted parts are resistant against acid and VE-water, so far these liquids haven't any negative effects on stainless steel in 1.4301 version (V2A)

Technical data	1000 ESR
Adjustable operating pressure	approx. 3 –12 bar
Spray/water flow rate	~ 1,1 – 2,4 l/min
Operating temperature	~ 95 °C in 60 sec.(8bar) at 12 bar appr. 80°C
Type of current	3P-N-PE/400V/50 cps
Nominal power consumption	10 KW
Capacity <ul style="list-style-type: none"> • Fresh water tank • Detergent tank • Bath 	60 liter 5 liter 30 liter
Connecting cable	7,5 m
Spray hose lance	5 m
Spray hose pistol	2 m
Dimensions (LxWxH)	109 x 73 x 118 cm
Dimensions of cleaning grid (LxW)	90x60 cm
Weight (empty)	approx. 100 kg
Water recycling	Yes with 50 µm filter
Load capacity of collector	Approx. 80 kg
Noise level	<70 dBA
Adjustable pressure	yes
Garden connection	yes
Temperature adjustment	On request
Tank emptying	yes
Concentrate reservoir	Option with metering pump
Changeable inserts	option

Technical modifications reserved.