



Technical data
Hot cleaning wash-stand 150/130 HC

With direct water connection and water outlet, is operating with primary pressure from external water supply

<i>Technical data</i>	<i>150 HC</i>	<i>130 HC</i>
Working pressure	Water supply	Water supply
Spray/water volume	~ 1,0 l/min	~ 0,7 l/min
Operating temperature	~ 90 °C in 60 sec	~ 75 °C in 90 sec
Type of current	3P-N-PE/400V/50/60Hz	1P-N-PE/230V/50Hz
Nominal power consumption	5 KW	3 KW
Filling quantities		
• Fresh water	n.a.	n.a.
• concentrate	n.a.	n.a.
• bath	25 liter	25 liter
Connecting cable	5 m	5 m
Spray hose lance	n.a.	n.a.
Spray hose pistol	2 m	2 m
Dimension (LxWxH)	76 x 60 x 110 cm	76 x 60 x 110cm
Dimension of cleaning grid (LxW)	70 x 50 cm	70 x 50 cm
Weight empty	approx.. 45 kg	approx. 45 kg
Filtering	n.a.	n.a.
Bath level control	n.a.	n.a.
Carrying capacity of slop collector	50 kg	50 kg
Noise level	<70 dBA	<70 dBA
Changeable inserts	Option	Option
Cleaning agent to be added	n.a.	n.a.
Mobile	n.a.	n.a.

Technical modifications reserved.