

1500 SR-DP

The Maintenance Allrounder
with Extra Power



Accessories not part of standard equipment

APPLICATION

ADVANTAGES

<p>In general</p>	<ul style="list-style-type: none"> ✓ Fast, gentle, and efficient ✓ Both climate friendly and health friendly ✓ Autonomous, mobile, can be used inside a workshop
<p>Parts cleaning</p>	<ul style="list-style-type: none"> ✓ Cleaning from precision parts up to 10 ton motor ✓ With or without cleaner, gentle on fragile surfaces ✓ Recycling of dirt water
<p>Machine cleaning</p>	<ul style="list-style-type: none"> ✓ Using the own emulsion ✓ Ideal for areas which are difficult to access or fragile ✓ Reduction of stillstand times
<p>Cleaning at and under vehicles</p>	<ul style="list-style-type: none"> ✓ Cleaning of all mechanical parts directly at the vehicle ✓ Ideal for areas which are difficult to access or fragile ✓ Complies with rules of German trade associations
<p>Application examples</p>	<ul style="list-style-type: none"> ✓ Cleaning tooling machines with own emulsion ✓ Oil filters, air filters, radiators, heat exchangers.... ✓ Degreasing prior to paint jobs or powder coating

Technical Data 1500 SR-DP

- Mobile and independent
- Extra power up to 14 bar
- With large parts cleaning collector
- Large selection of accessories
- With water recycling system
- With dosing device for cleaning agent
- For particularly high requirements and persistent soilings



With stainless steel options

Technical Data	1500 SR-DP
Working pressure	~ 4 - 14 bar
Working temperature	~ 95°C in 60 seconds
Spray-/water volume	~ 1.3 - 2.8 liters / minute
Type of current	3P-N-PE / 400V / 50Hz / 32A
Power consumption	15 KW
Filling capacity	60 liter tank 30 liter collector 5 liter concentrate tank
Automatic water level control tank	Standard
Dimensions	109 x 73 x 118 cm
Collector load capacity	80 kg
Water recycling	With 25µm filter
Weight (empty)	~ 120 kg
Noise level	< 70 dBA
Pressure control	Stepless, on the unit
Temperature control	Option 1000 ET
External suction	Option 1500 ASR-DP
Thermal disinfection	Not applicable
Dosing pump & control for cleaning agent	Options DE-DP & DE-ÜW
Quick change coupling device for tank fill	Gardena compatible
Connector cable	7.5 meters
Hoses	Spray hose lance 5 meters Spray hose pistol 2 meters
Chassis in custom colour	Option 1000 WF
Stainless steel upgrades	Options 1000 EW (collector), SR-EC (chassis), and 1000 ER (wheels)

Subject to technical modifications. As of August 1, 2019.