

1000 SC

The Robust One for Vehicles



APPLICATION

ADVANTAGES

In general	✓ Fast, gentle, and efficient
	✓ Both climate friendly and health friendly
	✓ Autonomous, mobile, can be used inside a workshop
Cleaning of large parts	✓ Up to 10 tons in combination with collector 1000 SRS
	✓ Gentle on fragile and complex surfaces
	✓ Often without chemistry or cleaners
Machine cleaning	✓ Using the own emulsion
	✓ Ideal for areas which are difficult to access or fragile
	✓ Reduction of stillstand times
Cleaning at and under vehicles	✓ Cleaning of all mechanical parts directly at the vehicle
	✓ Significantly cheaper than A1-brake cleaners
	✓ Complies with rules of German trade associations
Application examples	✓ Large parts from truck motor to plane turbines
	✓ Motorblocks, transmissions, axes, tanks, trains...
	✓ Degreasing prior to paint jobs or powder coating

Technical Data 1000 SC

- Mobile and independent
- 60 liters water tank
- Automatic water level control
- With standard lance and spray pistol
- Dosing device for cleaning agents
- Ideal in combination with our collectors



Technical Data	1000 SC
Working pressure	~ 7.5 bar
Working temperature	~ 95°C in 60 seconds
Spray-/water volume	~ 1.8 liters / minute
Type of current	3P-N-PE / 400V / 50Hz / 16A
Power consumption	10.1 KW
Filling capacity	60 liter tank 5 liter concentrate tank
Automatic water level control - tank	Standard
Dimensions	980 x 550 x 670 mm
Weight (empty)	~ 65 kg
Noise level	< 70 dBA
Doing pump for cleaner / concentrate	Option DE-DP
Water recycling	No water recycling in this unit Possible in combination with collector unit
Pressure control	No pressure control in this unit Possible on the lance with SR-DV
Temperature control	Option 1000 ET
Connector cable	7.5 meters
Hoses	Spray hose 5 meters, screwed tight to the device, with fixed lance
Chassis in custom colour	Option 1000 WF

Subject to technical modifications. As of August 13, 2021.