



1000 SRK

The Compact One

| APPLICATION | ADVANTAGES |
|---------------------------------------|--|
| In general | <ul style="list-style-type: none"> ✓ Fast, gentle, and efficient ✓ Both climate friendly and health friendly ✓ Autonomous, mobile, can easily be hauled into a vehicle |
| Parts cleaning | <ul style="list-style-type: none"> ✓ Cleaning from precision parts up to 10 ton motor ✓ With or without cleaner, gentle on fragile surfaces ✓ Low water consumption |
| Machine cleaning | <ul style="list-style-type: none"> ✓ Using the own emulsion ✓ Ideal for areas which are difficult to access or fragile ✓ Reduction of stillstand times |
| Cleaning at and under vehicles | <ul style="list-style-type: none"> ✓ Cleaning of all mechanical parts directly at the vehicle ✓ Significantly cheaper than A1-brake cleaners ✓ Complies with rules of German trade associations |
| Application examples | <ul style="list-style-type: none"> ✓ Cleaning of tooling machines ✓ Oil filters, air filters, radiators, heat exchangers.... ✓ Ideal for service companies and technicians - easy to transport |

Technical Data 1000 SRK

- Variants 1000 SRK-EA, 1000 SRK-AS and combination 1000 SRK-AS-EA
- EA: Uses direct external water supply
- AS: Enables the suction of liquids from a separate tank
- Small wheels at the handle allow for particularly easy loading and transportation



| Technical Data | 1000 SRK-AS | 1000 SRK-EA |
|-----------------------|--|--|
| Working pressure | ~ 3.0 - 7.5 bar | ~ 3.0 - 7.5 bar + pre-pressure Heating capacity is reduced for total pressures (pre-pressure + pump) above 8 bar. |
| Working temperature | ~ 95°C in 60 seconds | ~ 95°C in 60 seconds |
| Spray-/water volume | ~ 1.1 - 1.8 liters / min. | ~ 1.1 - 2.4 liters / min. |
| Type of current | 3P-N-PE/400V/50Hz/16A | 3P-N-PE / 400V / 50Hz / 16A |
| Power consumption | 10.1 KW | 10.1 KW |
| Water supply | Suction from separate tank | External water supply with pre-pressure of 2 - 6 bar |
| Dimensions | 920 x 480 x 450 mm | 920 x 480 x 450 mm |
| Weight (empty) | ~ 55 kg | ~ 55 kg |
| Noise level | < 70 dBA | < 70 dBA |
| Pressure control | Stepless, on the unit | Stepless, on the unit |
| Temperature control | Option 1000 ET | Option 1000 ET |
| External suction | Standard | Only with AS-EA |
| Filter | 25 µm | Only with AS-EA |
| Dosage pump cleaner | Not available | Option DE-DP |
| Connector cable | 7.5 meters | 7.5 meters |
| Hoses | Suction hose 5 meters Spray hose 5 meters | Suction hose only with AS-EA Spray hose 5 meters |
| Chassis custom colour | Option 1000 WF | Option 1000 WF |

Subject to technical modifications. As of August 13, 2021.